

Tsuneo MAKI et al., S.N. 10/532,852
Page 8

Dkt. 2271/74323

Listing of Claims

The following listing of claims will replace all prior versions, and listings, of claims in the subject application:

1. (currently amended) A belt conveyance apparatus comprising:

a drive roller;

a driven roller rotating in accordance with an operation of the drive roller;

a conveyance belt engaged with the drive roller for rotationally driving the conveyance belt and the driven roller, the conveyance belt being provided with a first bead and a second bead formed on an inner side thereof; and

driven roller support means for ~~movably~~ rotatably supporting the driven roller, the driven roller support means being configured to allow the driven roller to move in a thrust direction,

wherein, in operation, ends of the drive roller and the driven roller interface with the first bead and second bead of the conveyance belt so as to allow and restrict a deflection of the conveyance belt in the thrust direction, and the driven roller is movable in the thrust direction ~~against~~ according to a deflection of the conveyance belt.

2. (currently amended) The belt conveyance apparatus as claimed in claim 1, wherein the ~~bead is~~ first and second beads are formed on each side of the conveyance belt in a direction of width thereof, and a clearance between a first end of the driven roller and the driven roller support means on a side of the first end of the driven roller is greater than a sum of a first clearance between a second end of the driven roller and the second bead which is located on a

Tsuneo MAKI et al., S.N. 10/532,852
Page 9

Dkt. 2271/74323

side of the second end of the driven roller, a second clearance between a first end of the drive roller and the first bead which is located on a side of the first end of the drive roller, and a third clearance between a second end of the drive roller and the second bead which is located on a side of the second end of the drive roller.

3. (currently amended) The belt conveyance apparatus as claimed in claim 1, wherein ~~the bead~~ at least one of the first bead and second bead is provided on an inner side of the conveyance belt, and a groove is formed on a circumferential surface of the drive roller so that the ~~[[bead]]~~ at least one of the first bead and second bead is brought into engagement with the groove.

4. (currently amended) The belt conveyance apparatus as claimed in claim 1, wherein a coefficient of friction between an end portion of the drive roller and ~~the bead~~ at least one of the first bead and second bead is set smaller than a coefficient of friction of a center portion of the drive roller and the ~~[[bead]]~~ at least one of the first bead and second bead.

5. (currently amended) The belt conveyance apparatus as claimed in claim 4, wherein a taper is formed on an end surface of the drive roller so that, in an unoperated state, a non-tapered portion of the end surface overlaps a side surface of ~~the bead~~ at least one of the first bead and second bead.

6. (original) The belt conveyance apparatus as claimed in claim 5, further comprising a first rotational member constituting the center portion of the drive roller and a second rotational

Tsuneo MAKI et al., S.N. 10/532,852
Page 10

Dkt. 2271/74323

member constituting the end portion of the drive roller, wherein an outer diameter of the second rotational member is within a range of ± 1.0 mm of an outer diameter of the first rotational member.

7. (original) The belt conveyance apparatus as claimed in claim 5, wherein a taper angle of the taper with respect to the end surface of the drive roller is set in a range from 10 degrees to 45 degrees.

8. (original) The belt conveyance apparatus as claimed in claim 1, wherein an axis of the drive roller and an axis of the driven roller are substantially perpendicular to a direction of conveyance of a paper sheet, and the axis of the driven roller is inclined with respect to the axis of the drive roller.

9. (currently amended) The belt conveyance apparatus as claimed in claim 8, wherein ~~the bead~~ at least one of the first bead and second bead is formed on one side of an inner surface of the conveyance belt so that, in an operated stated, the ~~[[bead]]~~ at least one of the first bead and second bead interferes with a lower one of opposite ends of the driven roller in operation.

10. (currently amended) The belt conveyance apparatus as claimed in claim 9, wherein a taper is formed on an end surface of the drive roller so that, in an unoperated stated, a non-tapered portion of the end surface overlaps a side surface of the ~~[[bead]]~~ at least one of the first bead and second bead.

Tsuneo MAKI et al., S.N. 10/532,852
Page 11

Dkt. 2271/74323

11. (original) The belt conveyance apparatus as claimed in claim 10, wherein a taper angle of the taper with respect to the end surface of the drive roller is set in a range from 10 degrees to 45 degrees.

12. (previously presented) The belt conveyance apparatus as claimed in claim 1, wherein a frictional force in the thrust direction between the driven roller support means and the driven roller is smaller than a frictional force of the driven roller and the conveyance belt.

13. (previously presented) The belt conveyance apparatus as claimed in claim 1, wherein a coefficient of friction between the drive roller and the conveyance belt is greater than a coefficient of friction between the driven roller and the conveyance belt.

14. (previously presented) The belt conveyance apparatus as claimed in claim 1, further comprising pressing means for pressing the conveyance belt to the drive roller, wherein the pressing means is located at a position opposite to the drive roller with the conveyance belt interposed therebetween.

15. (currently amended) An image forming apparatus comprising:

image forming means for forming an image; and

a belt conveyance apparatus including:

a drive roller;

a driven roller rotating in accordance with an operation of the drive roller;

a conveyance belt engaged with the drive roller for rotationally driving the conveyance

Dkt. 2271/74323

Tsuneo MAKI et al., S.N. 10/532,852

Page 12

belt and the driven roller, the conveyance belt being provided with a first bead and a second bead formed on an inner side thereof; and

driven roller support means for ~~movably~~ rotatably supporting the driven roller, the driven roller support means being configured to allow the driven roller to move in a thrust direction,

wherein, in operation, ends of the drive roller and the driven roller interface with the first bead and second bead of the conveyance belt so as to allow and restrict a deflection of the conveyance belt in the thrust direction, and the driven roller is movable in the thrust direction ~~against~~ according to a deflection of the conveyance belt.

16. (currently amended) The image forming apparatus as claimed in claim 15, wherein the ~~bead is~~ first and second beads are formed on each side of the conveyance belt in a direction of width thereof, and a clearance between a first end of the driven roller and the driven roller support means on a side of the first end of the driven roller is greater than a sum of a first clearance between a second end of the driven roller and the second bead which is located on a side of the second end of the driven roller, a second clearance between a first end of the drive roller and the first bead which is located on a side of the first end of the drive roller, and a third clearance between a second end of the drive roller and the second bead which is located on a side of the second end of the drive roller.

17. (currently amended) The image forming apparatus as claimed in claim 15, wherein ~~the bead~~ at least one of the first bead and second bead is provided on an inner side of the conveyance belt, and a groove is formed on a circumferential surface of the drive roller so that

Tsuneo MAKI et al., S.N. 10/532,852
Page 13

Dkt. 2271/74323

the ~~[[bead]]~~ at least one of the first bead and second bead is brought into engagement with the groove.

18. (currently amended) The image forming apparatus as claimed in claim 15, wherein a coefficient of friction between an end portion of the drive roller and ~~the bead~~ at least one of the first bead and second bead is set smaller than a coefficient of friction of a center portion of the drive roller and the ~~[[bead]]~~ at least one of the first bead and second bead.

19. (currently amended) The image forming apparatus as claimed in claim 18, wherein a taper is formed on an end surface of the drive roller so that, in an unoperated state, a non-tapered portion of the end surface overlaps a side surface of the ~~[[bead]]~~ at least one of the first bead and second bead.

20. (original) The image forming apparatus as claimed in claim 19, further comprising a first rotational member constituting the center portion of the drive roller and a second rotational member constituting the end portion of the drive roller, wherein an outer diameter of the second rotational member is within a range of ± 1.0 mm of an outer diameter of the first rotational member.

21. (original) The image forming apparatus as claimed in claim 19, wherein a taper angle of the taper with respect to the end surface of the drive roller is set in a range from 10 degrees to 45 degrees.

Tsuneo MAKI et al., S.N. 10/532,852
Page 14

Dkt. 2271/74323

22. (original) The image forming apparatus as claimed in claim 15, wherein an axis of the drive roller and an axis of the driven roller are substantially perpendicular to a direction of conveyance of a paper sheet, and the axis of the driven roller is inclined with respect to the axis of the drive roller.

23. (original) The image forming apparatus as claimed in claim 22, wherein the bead is formed on one side of an inner surface of the conveyance belt so that, in an operated stated, the bead interferes with a lower one of opposite ends of the driven roller in operation.

24. (currently amended) The image forming apparatus as claimed in claim 23, wherein a taper is formed on an end surface of the drive roller so that, in an unoperated stated, a non-tapered portion of the end surface overlaps a side surface of the ~~[[bead]]~~ at least one of the first bead and second bead.

25. (original) The image forming apparatus as claimed in claim 24, wherein a taper angle of the taper with respect to the end surface of the drive roller is set in a range from 10 degrees to 45 degrees.

26. (previously presented) The image forming apparatus as claimed in claim 15, wherein a frictional force in the thrust direction between the driven roller support means and the driven roller is smaller than a frictional force of the driven roller and the conveyance belt.

27. (previously presented) The image forming apparatus as claimed in claim 15, wherein

Tsuneo MAKI et al., S.N. 10/532,852
Page 15

Dkt. 2271/74323

a coefficient of friction between the drive roller and the conveyance belt is greater than a coefficient of friction between the driven roller and the conveyance belt.

28. (previously presented) The image forming apparatus as claimed in claim 15, further comprising pressing means for pressing the conveyance belt to the drive roller, wherein the pressing means is located at a position opposite to the drive roller with the conveyance belt interposed therebetween.